




ACAD GENERATED DRAWING. DON'T CHANGE BY HAND.





CIRCUIT DIAGRAM
回路图



RECOMMENDED P.C.B. LAYOUT

安装尺寸图

规格 Specifications			
额定负荷 Rating	DC 12V/50mA		
接触电阻 Contact Resistance	100mΩ max.		
绝缘电阻 Insulation resistance	DC100V 60S 100MΩ min.		
抗电强度 Dielectric strength	AC250V(50-60HZ) 60S min.		
操作力 Operation force	≤180±30gf	≤300±50gf	
寿命试验 Operating Life	50,000 cycles	30,000 cycles	
行程 Travels	0.25±0.1mm		



PRODUCT NO. : 1TS002*****-CT

轻触开关
3X6系列
外形:
A=插脚
B=贴片
C=贴片带柱
D=贴片2.5高
K=贴片带柱8.8
L=贴片10.2

按钮颜色:
底座颜色:
盖板颜色:
操作力度:
手感:
产品高度(H):

130=130±20gf
160=160±30gf
180=180±30gf
220=220±40gf
250=250±50gf
300=300±50gf

0=常规
1=大手感
2=小手感
3=特殊手感

材质:
0=PA66
1=CP+PPA
2=LCP
3=PA66+PPA
4=新增材质
依次增加

非编带, 不启用

ITEM	PART NAME	QUANTITY	MATERIAL	FINISH
5	ACTUATOR	1	LCP	YELLOW
4	COVER	1	STAINLESS STEEL	NATURAL
3	DOME	1	STAINLESS STEEL	Ag-PLATED
2	HOUSING	1	PPA	WHITE
1	TERMINAL	1	BRASS	Ag-PLATED/0.2μm
NAME(INTENDED USE) 3X6 SMT SERIES(POST) TACT SWITCH				
HON YUAN HON YUAN PRECISION IND. CO.,LTD. SHENZHEN, CHINA, R.O.C.				
TITLE: PRODUCT DRAWING				
PART NO.(INTENDED USE) 1TS002C****-****-***1				
APPD: ZO 2015/11/12				
DWG NO.: 1TS002C				
CHKD: M.H.LI 2015/11/12				
DR: W.P.LU 2015/11/11				
SCALE SHEET REV.				
10/1 2/4 D				