ACAD GENERATED DRAWING. DON'T CHANGE BY HAND.

REV	ECN NO.	APPD
A	HC-17-0070	PRIOJOM





安装参考尺寸

规格 Specifications

额定负荷 Rating	DC 12V/50mA
接触电阻Contact Resistance	100mΩ max.
绝缘电阻Insulation resistance	DC100V 60S 100MΩ min.
抗电强度Dielectric strength	AC250V(50~60HZ) 60S min.
操作力Operation force	250±50gf
寿命试验Operating Life	100,000 cycles
行程Travels	0.20±0.1mm







原理图

PRODUCT NO.: 1TS008B***-****-**** - CT

- 轻触开关
- 3X4立式小龟系列
- 外形:
- 按钮颜色:
- 底座颜色:
- 盖板颜色:
  - ⇩ 初始颜色，则不启用
- 操作力度: 180=180gf, 250=250gf
- 手感: 0=常规, 1=大手感, 2=小手感
- 产品高度(H): 200=2.00mm
- 材料: 0=初始材料, 1=新增材料依次增加
- 编带: 非编带,不启用

ITEM	PART NAME	QUANTITY	MATERIAL	FINISH
F	盖板	1	不锈钢	酸洗
E	按钮	1	LCP	黑
D	防尘膜	/	0.05	/
C	弹片	2	进料不锈钢	镀银
B	底座	1	LCP	黑
A	卡件	1	磷铜	镀银

X. ± 0.3	X.° ± 3°
.X ± 0.2	.X° ± 2°
.XX ± 0.1	.XX° ± 1°
.XXX ± 0.05	.XXX° ± 0.5°

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF HON YUAN PRECISION IND. CO., LTD. AND SHALL NOT BE REPRODUCED, COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF HON YUAN PRECISION IND. CO., LTD.

UNITS: MM
MAT'L:
FINISH:
Q'TY:

NAME(INTENDED USE): 四脚小龟
PART NO.(INTENDED USE): 1TS008B***-****-****
APPD: ZD 2017/8/18
CHKD: M.H.Li 2017/8/18
DR: Y.Y.Chen 2017/8/18

HON YUAN
HON YUAN PRECISION IND. CO.,LTD.
SHENZHEN, CHINA, P.R.C.

TITLE: PRODUCT DRAWING
DWG NO.: 1TS008B

SCALE	SHEET	REV.
10/1	1/1	A