





| REV | ECN NO. | APPD |
|-----|------------|---------|
| A | HC-18-0072 | PRIOUOM |


规格 Specifications

| | | |
|---------------------------|--------------------------|--------------|
| 额定负荷 Rating | DC 12V/50mA | |
| 接触电阻Contact Resistance | 100mΩ max. | |
| 绝缘电阻Insulation resistance | DC100V 60S 100mΩ min. | |
| 抗电强度Dielectric strength | AC250V(50~60Hz) 60S min. | |
| 操作力Operation force | 160±30gf | 250±50gf |
| 寿命试验Operating life | 100,000cycles | 70,000cycles |
| 行程Travels | 0.13±0.05mm | |




CIRCUIT DIAGRAM

回路图



RECOMMENDED P.C.B. LAYOUT

安装尺寸图



PRODUCT NO.: 1TS017A*****

轻触开关

3.7X3.7系列

外形:

A=平脚

B=弯脚

触点颜色:

贴膜颜色:

操作力度:

初始颜色

则不启用

手感:

0=常规(弹片)

1=大手感(弹片)

2=小手感(弹片)

3=特殊手感(弹片)

其它:

CT=编带(非编带,不启用)

材质:

0=初始材质

1=新增材质

依次增加

产品高度(H):

040=0.40mm

| 4 | FILM | 1 | POLYAMIDE | WHITE |
|--|--------------|----------------------------------|-----------------|-----------|
| 3 | DOVE | 1 | STAINLESS STEEL | Ag-PLATED |
| 2 | HOUSING | 1 | POLYAMIDE | BLACK |
| 1 | TERMINAL | 1 | BRONZE | Ag-PLATED |
| ITEM | PART NAME | QUANTITY | MATERIAL | FINISH |
| X. ± 0.2 | X. ± 3' | UNITS | MM | |
| .X ± 0.1 | .X' ± 2' | MAT'L | | |
| .XX ± 0.05 | .XX' ± 1' | FINISH | | |
| .XXX ± 0.03 | .XXX' ± 0.5' | | | |
| NAME(INTENDED USE) | | HON YUAN | | |
| 3.7X3.7 | | HON YUAN PRECISION IND. CO.,LTD. | | |
| TACT SWITCH | | SHENZHEN, CHINA. | | |
| PART NO.(INTENDED USE) | | TITLE: | | |
| 1TS017A-*****0 | | PRODUCT DRAWING | | |
| APPD: ZO 2018-8-16 | | DWG NO.: 1TS017A | | |
| CHKD: M.H.LI 2018-8-16 | | | | |
| DR.Y.Y.Chen 2018-8-16 | | | | |
| Q'TY | | | | |
| THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF HON YUAN PRECISION IND. CO., LTD. AND SHALL NOT BE REPRODUCED, COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF HON YUAN PRECISION IND. CO., LTD. | | | | |