

ACAD GENERATED DRAWING. DON'T CHANGE BY HAND.

REV	ECN NO.	APPD
A	HC200100	ZO


### 规格 Specifications

额定负荷 Rating	DC 12V/50mA
接触电阻 Contact Resistance	500mΩ max.
绝缘电阻 Insulation resistance	DC100V 60S 100MΩ min.
抗电强度 Dielectric strength	AC250V(50~60HZ) 60S min.
操作力 Operation force	160±30gf
寿命试验 Operating Life	200,000 cycles
行程 Travels	0.12±0.05mm


PRODUCT NO. : 1TS032A\*\*\*-\*\*\*-\*\*\*-\*\*

轻触开关	其它:
3.8X1.9系列	CT=编带(非编带,不启用)
外形:	材质:
A=侧按	0=初始材质
	1=新增材质
	依次增加
	产品高度(H):
	155=1.55mm
按钮颜色:	
塑胶上盖颜色:	
底座颜色:	
初始颜色 则不启用	
操作力度:	
160=160gf	
180=180gf	
240=240gf	
手感:	
0=常规(弹片)	
1=大手感(弹片)	
2=小手感(弹片)	
3=特殊手感(弹片)	

LAND PATTERN PLAN  
印刷电路板焊盘参考图



8	STEM	1	POLYAMIDE	BLACK
7	METAL COVER	1	BRASS	Ag-PLATED
6	PLASTIC COVER	1	POLYAMIDE	BLACK
5	KNOB	1	POLYAMIDE	BLACK
4	FILM	1	POLYAMIDE	WHITE
3	DOME	3	SUS301	Ag-PLATED
2	HOUSING	1	POLYAMIDE	BLACK
1	TERMINAL	1	PHOSPHOR BRONZE	Ag-PLATED
ITEM	PART NAME	QUANTITY	MATERIAL	FINISH

ITEM	P/N	PART NAME		Q'TY	MAT'L	FINISH	SPECIFICATION	REMARK				
X. ± 0.2	X.* ± 3'	UNITS MM	MAT'L	NAME(INTENDED USE)		HON YUAN HON YUAN PRECISION IND. CO.,LTD. SHENZHEN, CHINA.						
.X ± 0.1	.X* ± 2'			2X3 SIDE PUSH SERIES LASER WATERPROOF								
.XX ± 0.05	.XX* ± 1'	FINISH	MAT'L	PART NO.(INTENDED USE)		TITLE:						
.XXX ± 0.03	.XXX* ± 0.5'			1TS032A-1600-2903		PRODUCT DRAWNG						
THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF HON YUAN PRECISION IND. CO., LTD. AND SHALL NOT BE REPRODUCED, COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF HON YUAN PRECISION IND. CO., LTD.				Q'TY	CHKD:	DWG NO.:			SCALE	SHEET	REV.	
					ZO 8/27'2020		1TS032A					
					M.H.Li 8/27'2020							
					DR:	WP.Lu 8/27'2020						

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF HON YUAN PRECISION IND. CO., LTD. AND SHALL NOT BE REPRODUCED, COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF HON YUAN PRECISION IND. CO., LTD.

(Back View)